

KD13-1000-A - COMPRESOR, QUINCY - ULTRAQUIP 270 (WELLHEAD)

Consist:

Skid mounted with drip rail
Model 270 QRNG compressor
20 hp TEFC motor 480/3/60 256t frame
Belt drive and guard
Discharge relief valve
After cooler Oversize
Control panel with across the line starter and
24 vdc power supply for control voltage (panel
auto start stop based on pressure settings
Opifc-a Murphy gages Lights to indicate mode or
shutdown.
Kenco oil reservoir 5 gal with Murphy control valve and sight glass
Maximum Suction/Discharge Pressure (PSIG) 50/125



KDE-240 VAPOR RECOVERY UNIT (VRU) 10HP QUINCY 240

Consist:

Quincy QRNG 240 single stage compressor
Capability: 50 mcf/d at 5 oz inlet and 80psi discharge
12X48 Inlet scrubber with stainless steel mess pad, high level kill
Ebara self priming stainless steel 2 hp liquids pum
discharge relief valve

GasFlo 1050 controller unit has one analog input for suction control
6 digital inputs for gauge operation unit includes the following
Enclosure
10 hp motor starter
Motor overload
Two line display
Membrane keypad
3 psi 4-20 ma sensor
Internal power supply
200 ft suction cable
Programable controller will on extra relay
10 hp Class 1 div 2 460 volt 3 phase motor
All mounted on a 4X6 skid with ecology drip rail and 4 point loading eyes



KD13-4125-A - COMPRESOR, QUINCY - ULTRAQUIP 4125 (WELLHEAD)

Consist:

Skid mounted with drip rail
Model 4125 QRNG compressor
30 hp TEFC motor 480/3/60 256t frame
Belt drive and guard
Discharge relief valve
After cooler Oversize
Control panel with across the line starter and
24 vdc power supply for control voltage (panel
auto start stop based on pressure settings
Opifc-a Murphy gages Lights to indicate mode or
shutdown.
Kenco oil reservoir 5 gal with Murphy control valve and sight glass
Maximum Suction/Discharge Pressure (PSIG) 50/125

